

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

Claim 1 (Currently Amended): Throttle flap valve having an essentially ring-shaped, elastic seal element (4) that surrounds an axial opening, having a valve disk (6) disposed to rotate in the axial opening, crosswise to the axial direction, having means for turning the valve disk (6) between the open and the closed positions, to control a flow of fluid through the opening, having at least two valve housing parts (5) that essentially surround the seal element (4) in ring shape, which surround two flanges (3) connected with an inflow (1) and an outflow (2), whereby conical contact surfaces of the flanges (3) and/or the valve housing parts (5) work together in such a manner that the flanges (3) are pressed axially against the seal element (4), forming a seal, by means of the valve housing parts (5), in the assembled state ready for operation, wherein the flanges (3) are rigidly connected with the valve housing parts (5), forming a positive

lock, in each instance, and wherein the flanges (3) are shaped to have rotation symmetry.

Claim 2 (Previously Presented): Throttle flap valve according to claim 1, wherein the valve housing parts are configured as two clamp halves (5).

Claim 3 (Currently Amended): Throttle flap valve according to claim 2, wherein the ~~inner surfaces of the~~ clamp halves (5) ~~that are~~ have inner surfaces in contact with the seal element (4) have comprising two ring-shaped depressions (10) for accommodating ~~that surround~~ the flanges (3), in each instance.

Claim 4 (Previously Presented): Throttle flap valve according to claim 3, wherein the depressions (10) are beveled at the edges (11).

Claim 5 (Currently Amended): Throttle flap valve according to claim 1, wherein ~~the flanges (3) are~~ each flange is configured to narrow conically towards the outside.

Claim 6 (Previously Presented): Throttle flap valve according to claim 1, wherein the valve housing parts (5) are configured so that they can be connected with screws (13) and nuts (14).

Claim 7 (Previously Presented): Throttle flap valve according to claim 1, wherein the valve housing parts (5) are configured with two ring-shaped recesses (8) that lie radially opposite one another, for accommodating valve disk shafts (7) of the valve disk (6).

Claim 8 (Previously Presented): Throttle flap valve according to claim 1, wherein the means for turning the valve disk (6) is a hand wheel.

Claim 9 (Previously Presented): Throttle flap valve according to claim 1, wherein the means for turning the valve disk (6) is an automatic setting element.

Claim 10 (Canceled).

Claim 11 (Currently Amended): Method for assembling a throttle flap valve according to claim 1, wherein in a first step, the seal element (4) is set onto the valve disk (6), ~~that~~ wherein in a second step, sleeves (9) are set onto valve disk shafts (7) of the valve disk (6), ~~that~~ wherein in a third step, the valve disk (6) provided with the seal element (4) and the sleeves (9) is placed between the flanges (3), ~~that~~ wherein in a fourth step, the valve housing parts (5) are placed around the flanges (3), ~~that~~ wherein in a fifth step, the valve disk shafts (7) of the valve disk (6) are oriented in a desired angle orientation, ~~that~~ wherein in a sixth step, the adjustable means (13, 14) for applying contracting radial and axial forces to the sealing element (4) are adjusted until the flanges (3) are rigidly connected with the clamp halves (5), forming a positive lock, and ~~that~~ wherein in a last step, the means for turning the valve disk (6) are affixed.